



control solutions

TERACOM

TCW122B-CM Ethernet controller



Overview

TCW122B-CM is an Ethernet controller for remote environmental monitoring and control. It has 2 digital, 2 analog inputs and 1-Wire interface for up to 2 temperature/humidity sensors.

The controller has 2 relays with normally open and normally closed contacts.

The relays can be activated either remotely or locally. The remote activation includes WEB interface or M2M protocols – SNMP and HTTP API. The local activation is possible from a status of monitored parameter (temperature, humidity, analog voltage and dry contact). Only one parameter can manage the relay at the same time.

For every monitored parameter e-mail and/or SNMP trap can be sent as an alert for previous set alarm conditions.

Applications

- **Remote environmental monitoring** – The device can monitor temperature and humidity in server rooms, data centers, mobile operators facilities room, offices etc.
- **Remote control of electric devices** - With its 2 relays, the device can control independently 2 electric devices. This can be done either by command through embedded WEB server or by some dedicated application, for example, TCW Control.
- **Home and office alarm systems** – The device can be set up to send e-mail and SNMP traps alerts in case of an alarm condition for temperature/humidity and digital/analog inputs.
- **SCADA systems** - With its supported M2M protocols, the device can be easily integrated into supervisory control and data acquisition systems.

Interfaces



10 Mbit
Ethernet



2x
Digital Inputs



0-60V
2x
Analog Inputs



2x
Relay Outputs



2x
1-Wire
Sensors

Basic features

- Embedded WEB server for configuration and control;
- „Dry contact“ and „Logic level“ modes for digital inputs;
- SNMP v1 support;
- SNMP traps for alarm conditions;
- SMTP without SSL/TLS support;
- Emails on alarm conditions;
- HTTP API commands support;
- XML status report file;
- HTTP and SNMP port changing;
- Remote firmware update.



control solutions

TERACOM

TCW122B-CM - Ethernet controller

Short specification

Supply voltage, VDC	12±2
Maximum current (with both relays ON), mA	200
Weight, g	110
Dimensions, mm	107 x 72 x 32
Operating temperature, °C	0 to 40
Maximum humidity in 0 to 31°C range, %RH	80
Maximum humidity at 40°C (linear slope between 31-40°C), %RH	50
Minimum high-level input voltage for digital inputs, VDC	+ 2.5
Maximum low-level input voltage for digital inputs, VDC	+ 0.8
Maximum input voltage for digital inputs, VDC	+ 5.5
Supply voltage for 1-wire bus (VDD), VDC	5.3 ± 0.2
Maximum output current for 1-wire bus (VDD), A	0.2
Analog inputs range, VDC	0 to 60
Maximum switchable current for relay contacts, A	3
Maximum switchable voltage for relay contacts, VAC/VDC	30/24

Typical application

Mobile device



INTERNET



Router



TCW122B-CM



TSH202



Supported sensors and detectors



Temperature



Humidity



Smoke
Detectors



Door and Window
Sensors



AC Voltage
Detector



Other Sensors
with Relay Output

Software

- TC Monitor
- TCW Control for Android
- TCW Control for iOS
- Third party software applications